

DESCRIPTION

Petrogulf EVO TRANS Type A is high quality automatic transmission fluids based on highly refined base stocks and carefully selected additives. These are designed for automatic transmissions and power steering systems of vehicles requiring General Motors for Type A specifications. They provide consistent, reliable, smooth and trouble-free operation of automotive transmission systems and exceptionally high oxidation resistance to oil degradation and keep automatic transmission clean. It is recommended to use in automatic transmissions of car & light trucks and On-highway & Off-highway heavy duty automatic transmissions.

KEY FEATURES & BENEFITS

- Good stability and oxidation stability
- Good low temperature fluidity, seal compatibility
- Foam control, corrosion and anti-wear properties
- Ensures friction durability, prolongs transmission life and promotes smooth shifting
- Provides shear stability
- Antirust properties and detergent qualities

PERFORMANCE LEVEL

- GM ATF Type A
- Allison C-3
- CAT TO-2

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES
Kinematic Viscosity @40°C, mm²/s	36.4
Kinematic Viscosity @100°C, mm²/s	7.4
Viscosity Index	175
Brookfield Viscosity @ -40°C cP	20000
Density, @ 15°C Kg/L	0.862
Pour Point °C	-45
Flash Point, (COC),°C	212
Color Visual	Red

**These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.*

PRODUCT GRADE	TYPE A
PRODUCT CODE	30800020000

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.