

DESCRIPTION

Petrogulf EAGLE 4T Oil is a series of synthetic base, shear-stable, multigrade, multifunctional lubricants developed specifically for gasoline motorcycle engines, clutches and gearboxes working under severe duty conditions. Synthetic base technology and carefully selected additives provide excellent protection against wear, deposits formation and thermal breakdown, keeping the performance throughout the full oil service life.

FEATURES & BENEFITS

- Full protection for engine, clutch and transmission
- High thermal stability and oxidation resistance
- Long engine life
- Low oil consumption
- Optimized frictional properties that deliver smooth clutch operation
- Reduced engine wear and deposits even in adverse conditions
- Wide operating conditions from mild to severe

APPLICATIONS

Petrogulf Eagle 4T Oil is highly recommended for use in four-stroke gasoline motorcycle Engine, Clutch and Gear (ECG) applications such as Honda, Suzuki, Kawasaki, Yamaha, Bajaj and other motorcycles that require the specifications below

PERFORMANCE LEVELS

- API SL, JASO MA2

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES			
SAE Grade	10W-30	10W-40	20W-40	20W-50
Kinematic Viscosity @40°C, mm ² /s	69.2	99.2	124.0	160.1
Kinematic Viscosity @100°C, mm ² /s	11.0	14.4	14.5	18.5
Viscosity Index	150	150	118	130
Density @ 15°C Kg/L	0.862	0.866	0.871	0.875
Pour Point, °C	-36	-36	-30	-30
Flash Point ,(COC), °C	220	224	230	234
CCS Viscosity, CP	5200	6400	6200	7500
CCS temp °C	-25	-25	-15	-15

*These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.

SAE GRADE	10W-30	10W-40	20W-40	20W-50
PRODUCT CODE	32303030011	32303030012	32303030016	32303030017

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.