

DESCRIPTION

Petrogulf EAGLE 4T Oil is a series of premium, fully synthetic, shear-stable, multigrade, multifunctional lubricants developed specifically for gasoline motorcycle engines, clutches and gearboxes working under severe duty conditions. Its high frictional properties guarantee the clutch engagement for enhanced acceleration. Full Synthetic formulation and carefully selected additives provide excellent protection against wear, deposits formation and thermal breakdown, keeping the performance throughout the full oil service life

FEATURES & BENEFITS

- Excellent oxidation stability under exposure to high operating temperature
- Optimized frictional properties that deliver smooth clutch operation
- Protects vital gear & clutch components to maximize their service life
- Provides exceptional protection against rust and keeps engine parts protected from wear
- Provides long drain intervals - Reduced fuel consumption (SAE 10W-30)
- Wide operating conditions from mild to severe

APPLICATIONS

Petrogulf Eagle 4T Oil is highly recommended for use in four-stroke gasoline motorcycle Engine, Clutch and Gear (ECG) applications such as Honda, Suzuki, Kawasaki, Yamaha, Bajaj and other motorcycles that require the specifications below

PERFORMANCE LEVELS

- API SN, JASO MA2

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES			
	10W-30	10W-40	20W-40	20W-50
SAE Grade	10W-30	10W-40	20W-40	20W-50
Kinematic Viscosity @40°C, mm ² /s	71.6	100.1	126.2	163.5
Kinematic Viscosity @100°C, mm ² /s	11.3	14.5	14.6	18.6
Viscosity Index	150	150	117	128
Density @ 15°C Kg/L	0.864	0.868	0.875	0.878
Pour Point, °C	-36	-36	-30	-30
Flash Point ,(COC), °C	222	226	234	240
CCS Viscosity, CP	5400	6500	6300	7600
CCS temp °C	-25	-25	-15	-15

*These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.

SAE GRADE	10W-30	10W-40	20W-40	20W-50
PRODUCT CODE	32349040011	32349040012	32349040016	32349040017

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.