

DESCRIPTION

Petrogulf EVO TRANS Multi OEM is Fully Synthetic Automatic Transmission Fluid designed specifically for use in passenger and commercial vehicle automatic transmission with outstanding performance in American, Japanese, Korean and European vehicles. It also meets Former DEXRON III & VI, FORD and major OEM commercial vehicle automatic transmission specifications.

KEY FEATURES & BENEFITS

- Suitable for multi vehicle Automatic Transmission
- Excellent friction durability and anti-shudder performance
- Extended long drain intervals
- Very good low temperature fluidity

PERFORMANCE LEVEL

EVO TRANS MULTI OEM is suitable for the following OEM and International specifications:

Aisin Warner AW-1	Mitsubishi SP-II, SP-III, ATF J2
Allison C-4, TES-295, TES-389	Nissan Matic-D, J, K, S, 402
Audi G 052 162, G 052 990, G 055 025	Saab 93 165 147
BMW 7045E, LA2634, LT 71141	Shell 3403, LA 2634, M-1375.4
Chrysler ATF's, Mopar AS68RC	Subaru ATF, ATF-HP
Dexron II, IID, IIE, IIIF, IIIG, IIH, VI	Suzuki 3317
Eso LT 71141	Texaco ETL-7045E, ETL
Ford Type FNR5, Mercon V	Toyota T-III & T-IV
Honda ATF-Z1	Toyota WS (JWS 3324)
Hyundai SP-II, SP-III, SPH-IV, NWS-9638	Voith 55.6335 XX (G607)
Idemitsu K17	Voith 55.6336 XX (G1363)
JASO 1-A	Volvo Pass Car (4-6 sp)
JWS 3309, 3324	Volvo 97340, 97341
Kia SP-II, SP-III, & SP IV	VW G 052 162, G 052 990, G 055 025
MAN 339F, 339 V1, 339 V2, 339 Z1, 339 Z2	ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A
Mazda ATF-M III, ATF-MV	16L, 17C
MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7	ZF TE-ML 14B
236.9, 236.10, 236.11	

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES
Kinematic Viscosity @40°C, mm ² /s	33.2
Kinematic Viscosity @100°C, mm ² /s	7.2
Viscosity Index	189
Density @ 15°C Kg/L	0.848
Pour Point °C	-51
Flash Point , (COC), °C	215
Color Visual	Red

*These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel injection is used.

PRODUCT GRADE	MULTI OEM
PRODUCT CODE	3084100000

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.