

DESCRIPTION

Petrogulf EVO TRANS STUO is designed to serve nearly the entire farm lubricating oil needs all year round in all types of tractor engines, transmissions, final drives, hydraulic system and brakes

APPLICATIONS

Petrogulf Evo Trans STUO is recommended for use in gasoline engines and other utility vehicles around the farm. It can be used as transmission oil, hydraulic oil, wet-brakes and power take-off clutches

FEATURES & BENEFITS

- Multi-application additive package enables use in engines, transmission, final drives and hydraulic system.
- Protection against acid, varnish, carbon deposits, formation of gums, and reduces oil thickening.
- Multi-viscosity characteristic ensures rapid oil circulation on start-up, preventing wear.
- Special friction modifier component that allows smooth action of the wet brakes and power take-off clutches

PERFORMANCE LEVELS

- | | | | |
|--------|---------|-------------------|---------------------------|
| • API | CE/SF | • Allison | C4 |
| • CCMC | D3/G3 | • John Deer | J-20A |
| • MI | L-2104D | • Ford | M2C 159B |
| • MB | 227.1 | • Massey Ferguson | M 1139 |
| • API | GL-4 | • ZF TE-ML | 06 page 3 & 4 Part B & 07 |
| • CAT | TO-2 | • Mac | EOK-2 |

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES	
	15W-40	20W-40
SAE Grade	15W-40	20W-40
Kinematic Viscosity @40 °C mm ² /s	110.1	126.5
Kinematic Viscosity @100°C mm ² /s	14.5	14.40
Viscosity Index	135	114
Density @ 15°C Kg/L	0.874	0.880
Pour Point °C	-30	-27
Flash Point ,(COC), °C	230	240
CCS Viscosity, CP	6400	7200
CCS temp °C	-20	-15
TBN, mgKOH/g	11.0	11.0

*These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.

SAE GRADE	15W-40	20W-40
PRODUCT CODE	31811000015	31811000016

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.