

DESCRIPTION

Petrogulf Mould Release F is based on special mineral oil raffinates which contain rust inhibiting and separating agents. They form a chemical-physical separating film which prevents the adhesion between formwork and concrete.

FEATURES & BENEFITS

- Easy and clean separation of formwork and concrete
- Flawless concrete surfaces
- Protection of formwork against corrosion and premature ageing
- Easy to process, user-friendly

Petrogulf Mould Release F is not water-soluble. It is ready-to-use and can be applied as a thin layer onto the clean formwork immediately. The formation of oil pools is to be avoided. Excess release agent must be removed.

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES
Kinematic Viscosity @40 °C mm ² /s	10.0
Density @ 15°C Kg/L	0.854
Pour Point °C	-33
Flash Point °C (COC)	170
Total Acid No, mg KOH/g	3.5

**These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel injection is used.*

PRODUCT CODE**3191700000****Handling, Health and Safety**

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.