


MINERAL
MOTORCYCLE ENGINE OIL

DESCRIPTION

Petrogulf POWER 2T is a mineral based two stroke motorcycle oils specifically designed for excellent engine protection and performance in high-speed engines. They guarantee superior control against exhaust system blocking and minimize exhaust smoke. These oils are suitable for oil-injection and premix systems and exceed requirements of leading manufacturers. Petrogulf Power 2T oils contain hydrocarbon diluents and can be used both in oil injection systems fitted to modern 2-stroke motorcycles and premix systems. The high amount of carefully selected additive components minimizes exhaust smoke reducing the environment impact.

KEY FEATURES & BENEFITS

- All 2 stroke motorcycle engines with oil injection or premix system.
- Recommended for high-performance air and water cooled 2 stroke engines.
- Oil formulation is carefully balanced and specifically tested in 2 stroke engines to prevent scuffing, ring sticking and deposit formation. The engine life is prolonged and the original level maintained.
- Specific burning characteristics allow fast adaptation to new driver requirements improving acceleration performances and increasing power output.

PERFORMANCE LEVELS

- Exceed JASO FC and the requirements of leading motorcycle manufacturers.

TYPICAL CHARACTERISTICS

TEST PARAMETER	TYPICAL VALUES
SAE Grade	30
Kinematic Viscosity @40 °C mm ² /s	67.1
Kinematic Viscosity @100°C mm ² /s	9.85
Viscosity Index	130
Density @ 15°C Kg/L	0.863
Pour Point , °C	-33
Flash Point °C (PMCC)	110

**These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel injection is used.*

PRODUCT GRADE	30
PRODUCT CODE	31300010001

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.