

### DESCRIPTION

**Petrogulf PRIME X Silver** is a high-quality lubricant that provides exceptional protection and performance for a wide range of vehicles. Formulated with top-grade virgin base oils and advanced additives, this engine oil ensures optimal engine cleanliness, reduced wear, and enhanced oxidation resistance

### KEY FEATURES & BENEFITS

- Suitable for use in both gasoline and light old diesel engines.
- Prevents the accumulation of dirt and deposits generated during high-temperature operations.
- Provides superior protection against wear, corrosion, and sludge build-up, ensuring longer engine life.
- Keeps the engine clean by preventing sludge and deposit formation.

### PERFORMANCE LEVELS

- API CC/SG

### TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES					
SAE Grade	20W-40	20W-50	25W-40	25W-50	25W-60	25W-70
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	124.7	163.7	129.7	169.7	237.7	317.7
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	14.6	18.6	14.8	18.8	22.4	27.6
Viscosity Index	118	128	116	125	115	116
Density, @ 15°C Kg/L	0.878	0.882	0.880	0.883	0.885	0.887
Pour Point °C	-27	-27	-21	-21	-21	-21
Flash Point, (COC), °C	240	244	240	244	246	248
CCS Viscosity, CP	6700	7200	9800	9700	9900	9800
CCS temp °C	-15	-15	-10	-10	-10	-10
TBN, mg KOH/g	5.49	5.49	5.49	5.49	5.49	5.49

*\*These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.*

SAE GRADE	20W-40	20W-50	25W-40	25W-50	25W-60	25W-70
PRODUCT CODE	30201010016	30201010017	30201010018	30201010019	30201010020	30201010021

### Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.