

**DESCRIPTION**

Petrogulf SPARK X Gold is shear stable API SJ category oil, formulated using highly refined GR I base oils and detergent inhibitor package having good piston cleanliness, wear corrosion resistance.

**KEY FEATURES & BENEFITS**

- Suitable for 2001 and older model petrol cars/pickups/vans
- Good engine cleanliness

**PERFORMANCE LEVELS**

- API SJ/CF

**TYPICAL CHARACTERISTICS**

PROPERTIES	TYPICAL VALUES	
	20W-40	20W-50
SAE Grade	20W-40	20W-50
Kinematic Viscosity @40 °C, mm <sup>2</sup> /s	124.1	163.2
Kinematic Viscosity @100 °C, mm <sup>2</sup> /s	14.5	18.6
Viscosity Index	118	128
Density, @ 15°C Kg/L	0.878	0.880
Pour Point °C	-27	-27
Flash Point, (COC), °C	240	244
Color, ASTM	L2.0	L2.5
CCS Viscosity, CP	6700	7100
CCS temp, °C	-15	-15
TBN, mg KOH/g	6.10	6.10
Sulphated Ash, %w/w	0.70	0.70

*\*These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.*

SAE GRADE	20W-40	20W-50
PRODUCT CODE	30101030016	30101030017

**Handling, Health and Safety**

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.