

DESCRIPTION

Petrogulf SPARK X Legend is mineral base multi-grade gasoline engine oil used in petrol / CNG turbocharged direct injection and multi-valve engines, recommended for most severe driving conditions such as motorways and dense city traffic. The advanced additive package neutralizes corrosive particles by preventing them from grouping together forming power-robbing sludge. It is highly shear-stable & its proprietary formula helps your vehicle to maintain maximum horse power by reducing harmful deposit formation.

KEY FEATURES & BENEFITS

- Extended drain capability
- Maximizes engine life through outstanding wear and deposit control under the most severe high and low temperature operating condition.
- Resisting oil degradation and protection against resultant engine damage under most severe high-temperature conditions.
- Protects against start up wear through exceptional low temperature fluidity.
- Excellent oil thickness retention under severe high temperature operating conditions
- Catalyst compatible with reduction in emission.

PERFORMANCE LEVELS

- API SM, JASO MA2
- ACEA A3/B3, A3/B4

TYPICAL CHARACTERISTICS

PROPERTIES	TYPICAL VALUES
SAE Grade	20W-50
Kinematic Viscosity @40°C, mm²/s	161.6
Kinematic Viscosity @100°C, mm²/s	18.60
Viscosity Index	130
Density, @ 15°C Kg/L	0.8755
Pour Point °C	-27
Flash Point (COC), °C	240
CCS Viscosity, CP	6700
CCS temp °C	-15
Approvals	API SM

**These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel injection is used.*

SAE GRADE	20W-50
PRODUCT CODE	30101050017

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.