

DESCRIPTION

Petrogulf Super Clean FLUSHING Oil is a low viscosity, straight mineral oil designed for flushing lubricating systems in general.

FEATURES & BENEFITS

- Pure oil compatible with all types of engine oils.
- Effective in cleansing mobile sludge from inner engine surfaces

APPLICATIONS

- After draining used sump oils from warm engines, the drain plugs should be reinserted and the engines refilled to the minimum oil level.
- Engines may then be run for 2 to 3 minutes under tick-over conditions, in order to circulate the oil and effectively wash the inner surfaces of the engine.
- Engines should not be run under load conditions while flushing oil is in use.
- After circulation, the engine should be switched off, the drain plug removed and the charge of flushing oil drained from the engine. If the flushing oil appears to be excessively dark in color, then the flushing operation may be repeated until only mild discoloration relative to the appearance of new flushing oil is observed. Finally, drain the flushing oil before replacing the drain plug and charging the engine with new lubricating engine oil.

TYPICAL CHARACTERISTICS

TEST PARAMETER	TYPICAL VALUES
Kinematic Viscosity @40 °C mm ² /s	30.5
Kinematic Viscosity @100°C mm ² /s	5.35
Viscosity Index	109
Density @ 15°C Kg/L	0.868
Pour Point, °C	220
Flash Point °C	-12

**These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel injection is used.*

PRODUCT CODE	31651000000
---------------------	--------------------

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.

www.pglube.com