

TUK TUK MOTOR OIL

MOTORCYCLE ENGINE OIL

DESCRIPTION

Petrogulf TUK-TUK Engine oils are specially designed keeping in view the high temperature operating conditions encountered in air cooled 2-wheeler/3-wheeler engines unlike in the case of passenger car engines, which are water cooled. Further these oils possess special frictional properties required for smooth operation of wet clutches used in these vehicles. These oils provide outstanding oxidation and wear protection for extended oil & engine life. These oils minimize engine deposits due to excellent sludge and varnish control. Being multigrade oils, these are suitable for use in all seasons. It is specially recommended for vehicles operating at high ambient temperatures and/or severe operating conditions.

KEY FEATURES & BENEFITS

- Maximizes engine life through outstanding wear and deposit control under the most severe high and low temperature operating condition.
- Reduces maintenance costs by maximizing the drain intervals, resisting oil degradation and protection against resultant engine damage under most severe high-temperature conditions.
- Protects against start up wear through exceptional low temperature fluidity.
- Minimizes oil consumption under all operating conditions through superior viscosity retention.
- Outstanding protection for 2-wheeler/3-wheeler gasoline engines.
- Suitable for use in Tuk Tuk (Autorickshaws) operating on Petrol fuel.

PERFORMANCE LEVELS

- API SJ/CF
- ACEA A3/B3/B4

TYPICAL CHARACTERISTICS

TEST PARAMETER	TYPICAL VALUES
SAE Grade	20W-50
Kinematic Viscosity @40 °C mm ² /s	168.0
Kinematic Viscosity @100°C mm ² /s	18.80
Viscosity Index	130
Density@15°C Kg/L	0.881
Pour Point ,°C	-27
Flash Point ,(COC), °C	230
CCS Viscosity, CP	7500
CCS temp °C	-15
Sulphated Ash,% w/w	0.8

**These characteristics are typical of current production. Whilst future production will conform to Petrogulf specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.*

PRODUCT GRADE	20W-50
PRODUCT CODE	30201000017

Handling, Health and Safety

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.
- PetroGulf will not accept liability if the product is used other than in manner or with the precautions, or for the purpose specified. Before the product is used other than directed advice should be obtained from PetroGulf local office.